



OPTION  
VALIDABLE  
ISO 11607-2

➤ **Continuous flow welding machine**  
specially designed for rotary sealing with touch screen.

### General characteristics

- 15 mm flat seal in 4 strips of 2 mm for sterilizable packaging
- Electronic control of sealing force and speed
- Temperature control from 0 to 220 °C
- Keyboard with soft alphanumeric keys
- 304 stainless steel and epoxy paint
- Two RS232 serial ports
- Choice of language
- Memorization of up to 6000 registers of welding parameters equivalent to 2000 welded bags
- 7" touch screen
- 2 RS232 serial ports, 1 Ethernet port, 1 PS2 port and 1 VGA port



OPTION  
VALIDABLE  
ISO 11607-2

#### Options

- Roll holder tray
- Roll holder complete with cutting device
- Label printer

#### Optional ISO 11607-2 standard:

**Blocking in case of non-compliance with any of the parameters used to qualify the sealer.**

**Temperature - Force - Time, are precisely controlled up to 60 times per second during the sealing cycle, in order to guarantee the repeatability of the sealing quality.**

In case of deviation from the defined parameters, the machine automatically stops working and triggers an acoustic alarm.

General Characteristics	H-LAN TOUCH
Welding width (mm)	15 multiligne (4 bandes de 2 mm)
Speed (according to type of packaging, cycle/min)	3 m/min à 13 m/min
Power supply	100 V – 110/115 V – 230/240 V
Power (w)	600
Dimensions (mm)	621 x 300 x 330
Weight (kg)	26