



➤ **Impulse clamps**  
**designed for sealing bags and materials:**  
**coated papers, laminates/plastics, single films, PE**

phone (33) 04 74 00 59 54 • [contact@o-r-a.eu](mailto:contact@o-r-a.eu)  
584 route de Saint-Bernard - 01600 Trévoux – France  
[www.o-r-a.eu](http://www.o-r-a.eu)



**General characteristics**

- Bi-active pulse clamps (top and bottom sealing)
- Digital temperature controller
- Electronically adjustable sealing and cooling times
- Low voltage power supply from the generator to the clamp
- Easy replacement of standard wear parts
- Clamps accessible for cleaning
- Cabinet on wheels

**Options**

Case for transport and storage

| Technical characteristics   | PSI 30 C             | PSI 40 C        |
|-----------------------------|----------------------|-----------------|
| Welding length (mm)         | 300                  | 400             |
| Welding width (mm)          | 4                    |                 |
| Dimensions (mm)             | 300 x 300 x 190      | 400 x 300 x 190 |
| Operating voltage           | 48 V                 |                 |
| Power (W)                   | 400                  |                 |
| Supply power                | 230 V mono + T 50 Hz |                 |
| Weight (kg) / clamp transfo | 1.8 / 9.5            | 2.3 / 9.5       |