

OPTION
VALIDABLE
ISO 11607-2

➤ **Continuous flow welding machine**
ergonomic design for welding complex materials such as:
paper/plastic, aluminium/plastic, coated paper, plastic laminates.

General features:

- 15 mm multi-line seal in 4 strips of 2 mm for sterilizable packaging
- Electronic control of sealing force and speed
- Temperature control from 0 °C to 200 °C
- Adjustable positioning of the seal in relation to the edge of the bag from 0 to 34 mm
- VIGITHERM for overheating safety
- Clock and calendar with automatic update
- Printing of the bag by matrix process with needles
- 4,3" color touch screen

Options

- Smooth table
- Roller table
- Label printer


 OPTION
VALIDABLE
ISO 11607-2
Optional ISO 11607-2 standard:

Blocking in case of non-compliance with any of the parameters used to qualify the sealer.

Temperature - Force - Time, are precisely controlled up to 60 times per second during the sealing cycle, in order to guarantee the repeatability of the sealing quality.

In case of deviation from the defined parameters, the machine automatically stops working and triggers an acoustic alarm.

Technical characteristics	PURA
Welding width (mm)	15 multilines (4 bands de 2 mm)
Speed (according to type of packaging, cycle/min)	10 m/min
Dimensions (mm)	553 x 264 x 192
power (w)	650
Frequency (Hz)	50-60
Power supply	230 V 50 Hz Mono
Weight (kg)	18